NSN 5925-00-702-7367

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-702-7367

Body Style:

Rectangular dimensional envelope

Overall Length:

8.500 inches

Overall Height:

4.500 inches

Overall Width:

6.688 inches

Unthreaded Mounting Hole Diameter:

1.375 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+910.0/+1560.0 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

50.000 at 500 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

NSN 5925-00-702-7367

Circuit Breaker Tripper - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A030a0

