NSN 5925-00-714-8823

Circuit Breaker - Page 1 of 2

Multipole-single actuator type

Body Style:

Body Length:



View Online at https://aerobasegroup.com/nsn/5925-00-714-8823

| 5.000 inches |
|--|
| Body Width: |
| 4.750 inches |
| Body Height: |
| 4.375 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 3.625 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 1.688 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 4.250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.500 inches |
| Boss Height: |
| 0.312 inches |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Thready Qty Per Inch (tpi): |
| 20 |
| Maximum Continuous Load Current Rating Per Pole: |
| 50.0 amperes ac all locations and 50.0 amperes dc all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 125.0 ac all locations and 125.0 dc all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 10000.0 ac all locations and 5000.0 dc all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Thermal-magnetic all locations |
| Trip Release Characteristic: |
| Instantaneous all locations and time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 138.0 all locations |
| Ultimate Trip Time Per Pole In Seconds: |
| 3600.000 all locations |

NSN 5925-00-714-8823 Circuit Breaker - Page 2 of 2



| Reset Method: |
|--|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At each pole |
| Thread Size: |
| 0.250 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 10.000 at 200 pct all locations and 210.000 at 200 pct all locations |
| Inclosure Protection Type For Which Designed: |
| Shockproof |
| Trip Release Ambient Tempurature Rating: |
| 50.0 degrees celsius all locations |
| Frequency In Hertz: |
| 400.0 all locations |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 6 clip |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A030a0 |
| |