## NSN 5925-00-718-7530

Circuit Breaker - Page 1 of 2

125.0 single location



View Online at https://aerobasegroup.com/nsn/5925-00-718-7530

**Body Style:** Single pole type **Body Length:** Between 4.740 inches and 4.760 inches **Body Width:** Between 1.020 inches and 1.040 inches **Body Height:** Between 2.820 inches and 2.840 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** Between 4.370 inches and 4.390 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 2.740 inches and 2.760 inches **Fragility Factor:** Moderately rugged **Pole Quantity:** 1 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 60.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

## **NSN 5925-00-718-7530** Circuit Breaker - Page 2 of 2



| Ultimate Trip Time Per Pole In Seconds:                                  |
|--|
| 175.000 single location and 550.000 single location                      |
| Reset Method:  |
| Manual   |
| Main Contact Tripping Mechanism Type:                                    |
| Trip free  |
| Manual Actuator Type And Quantity:                                       |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole one  |
| Internal Trip Release Configuration:                                     |
| Series trip single location  |
| Thread Size:   |
| 0.138 inches   |
| Trip Delay Time In Seconds Per Rated Continuous Current:                 |
| 39.000 at 200 pct single location and 105.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed:                            |
| General purpose  |
| Special Features:  |
| With handle extension construction kit                                   |
| Frequency In Hertz:  |
| 60.0 single location   |
| Unpackaged Unit Weight:  |
| 0.688 pounds   |
| Thread Series Designator:  |
| Unc  |
| Terminal Type And Quantity:  |
| 2 bus bar  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |