## NSN 5925-00-721-0195

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-721-0195

| Body Style:  |
|--|
| Single pole type   |
| Bushing Length:  |
| 0.250 inches   |
| Body Length:   |
| 2.187 inches   |
| Body Width:  |
| 0.750 inches   |
| Case Material:   |
| Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 1.437 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.812 inches   |
| Fragility Factor:  |
| Moderately rugged  |
| Mounting Surface To Terminal End Distance:                                   |
| 2.234 inches   |
| Pole Quantity:   |
| 1  |
| Mounting Facility Type And Quantity:   |
| 2 threaded hole  |
| Storage Type:  |
| General purpose warehouse  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Maximum Continuous Load Current Rating Per Pole:                             |
| 70.0 amperes ac single location and 70.0 amperes dc single location          |
| Operating Voltage Type And Rating Per Pole In Volts:                         |
| 120.0 ac single location and 30.0 dc single location                         |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:      |
| 3500.0 ac single location and 6000.0 dc single location                      |
| Circuit Protection Type:   |
| Overcurrent single location  |
| Trip Release Method:   |
| Thermal single location  |
| Trip Release Characteristic:   |
| Time delay single location   |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:       |
| 138.0 single location  |
| Reset Method:  |
| Manual   |

## **NSN 5925-00-721-0195** Circuit Breaker - Page 2 of 2



| Main Contact Tripping Mechanism Type:                                   |
|---|
| Trip free   |
| Manual Actuator Type And Quantity:                                      |
| 1 push button   |
| Actuator Function:  |
| Reset   |
| Actuator Position Designation:  |
| At pole one   |
| Internal Trip Release Configuration:                                    |
| Series trip single location   |
| Thread Size:  |
| 0.138 inches  |
| Trip Delay Time In Seconds Per Rated Continuous Current:                |
| 25.000 at 200 pct single location and 60.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed:                           |
| Explosion proof and fungus proof  |
| Trip Release Ambient Tempurature Rating:                                |
| 25.0 degrees celsius single location                                    |
| Frequency In Hertz:   |
| 60.0 single location  |
| Unpackaged Unit Weight:   |
| 0.240 pounds  |
| Thread Series Designator:   |
| Unc   |
| Terminal Type And Quantity:   |
| 2 screw   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A030a0  |
|   |
|   |