

View Online at <https://aerobasegroup.com/nsn/5925-00-721-0296>

**Overall Length:**

2.250 inches

**Overall Height:**

3.000 inches

**Overall Width:**

2.203 inches

**Case Material:**

Plastic

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.813 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Reset

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 60.000 at 200 pct all locations

**Inclsure Protection Type For Which Designed:**

Explosion proof

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0