

View Online at <https://aerobasegroup.com/nsn/5925-00-721-0296>

Overall Length:

2.250 inches

Overall Height:

3.000 inches

Overall Width:

2.203 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.813 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Reset

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 60.000 at 200 pct all locations

Inclsure Protection Type For Which Designed:

Explosion proof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0