NSN 5925-00-721-1330



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-721-1330 **Overall Length:** 1.750 inches **Overall Height:** 1.125 inches **Overall Width:** 0.625 inches **Case Material:** Metal **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 500.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Reset

Thread Size:
0.375 inches
Inclosure Protection Type For Which Designed:
Hermetically sealed

NSN 5925-00-721-1330

Circuit Breaker - Page 2 of 2



Frequency In Hertz:
400.0 single location
Precious Material:
Silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0