NSN 5925-00-721-1330

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-721-1330

Overall Length:

- 1.750 inches
- **Overall Height:**
- 1.125 inches
- **Overall Width:**
- 0.625 inches

Case Material:

Metal

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Thread Size:

0.375 inches

Inclosure Protection Type For Which Designed:

Hermetically sealed

NSN 5925-00-721-1330

Circuit Breaker - Page 2 of 2



Frequency In Hertz:

400.0 single location

Precious Material:

Silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0