

View Online at <https://aerobasegroup.com/nsn/5925-00-723-3774>

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

350.0 milliamperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

230.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

3.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.400 at 200 pct single location

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0