## NSN 5925-00-724-7017

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-724-7017

**Body Style:** 

Single pole type

**Body Length:** 

Between 3.709 inches and 3.729 inches

**Body Width:** 

Between 0.980 inches and 1.090 inches

Case Material:

Plastic

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 3.053 inches and 3.073 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

Between 2.740 inches and 2.760 inches

**Fragility Factor:** 

Moderately rugged

**Boss Height:** 

Between 0.146 inches and 0.166 inches

**Mounting Surface To Terminal End Distance:** 

3.329 inches

**Pole Quantity:** 

**Arc Quenching Method:** 

Magnetic blowout

**Mounting Facility Type And Quantity:** 

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

**Circuit Protection Type:** 

Overcurrent single location

**Trip Release Method:** 

Magnetic-hydraulic single location

**Trip Release Characteristic:** 

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

150.0 single location

## NSN 5925-00-724-7017

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
nternal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
7.000 at 200 pct single location and 15.000 at 200 pct single location
nclosure Protection Type For Which Designed:
Explosion proof and fungus proof and moisture proof and shock resistant and vibration resistant
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
9.750 ounces
Thread Series Designator:
Jnc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A030a0