

View Online at <https://aerobasegroup.com/nsn/5925-00-727-2624>

Overall Length:

4.670 inches

Overall Height:

9.380 inches

Overall Width:

4.130 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.094 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded stud

Thready Qty Per Inch (tpi):

16

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.500 at 300 pct all locations and 0.600 at 400 pct all locations

Trip Release Ambient Temperature Rating:

35.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0