## NSN 5925-00-727-7552

Circuit Breaker - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5925-00-727-7552

Multipole-single actuator type
Body Length:
6.500 inches
Body Width:
4.125 inches
Body Height:
3.875 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.938 inches
Center To Center Distance Between Terminals Parallel To Width:
1.375 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.312 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Boss Height:
0.187 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
100.0 amperes ac all locations and 100.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations and 250.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
15000.0 ac all locations and 10000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:

Instantaneous all locations and time delay all locations

## **NSN 5925-00-727-7552** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1200.0/+1400.0 ac all locations and +1200.0/+1400.0 dc all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
300.000 at 200 pct all locations and 900.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 quick disconnect, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0