NSN 5925-00-727-7574

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-727-7574

view Offiline at https://defobasegroup.com/histi/0920-00-727-737-4
Body Style:
Rectangular dimensional envelope
Overall Length:
22.000 inches
Overall Height:
12.000 inches
Overall Width:
12.781 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
1600.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+4000.0/+12000.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:

Trip Release Ambient Tempurature Rating:

0.041 at 200 pct all locations and 0.045 at 200 pct all locations

50.0 degrees celsius all locations

NSN 5925-00-727-7574

Circuit Breaker Tripper - Page 2 of 2



60.0 all locations

Terminal Type And Quantity:

6 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0