NSN 5925-00-728-9602

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-728-9602

Body Style:
Single pole type
Bushing Length:
Between 0.235 inches and 0.250 inches
Body Length:
2.189 inches
Body Width:
0.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
Between 1.160 inches and 1.220 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.800 inches and 1.820 inches
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
Between 2.340 inches and 2.400 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac single location and 15.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
120.0 ac single location and 30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
6000.0 ac single location and 6000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-00-728-9602 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
18.000 at 200 pct single location and 47.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Shockproof and vibration resistant and corrosion resistant and explosion proof and arc resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
3.250 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0