NSN 5925-00-729-9853

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-729-9853

Body Style:

Multipole-single actuator type

Body Length:

6.000 inches

Body Width:

4.125 inches

Body Height:

3.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.512 inches

Center To Center Distance Between Terminals Parallel To Width:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.844 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Boss Height:

0.219 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-00-729-9853 Circuit Breaker - Page 2 of 2



	Method:
Manua	
	Contact Tripping Mechanism Type:
Trip fr	
	al Actuator Type And Quantity:
1 togg	
	tor Function:
Trip-re	
	tor Position Designation:
At pole	
	Delay Time In Seconds Per Rated Continuous Current:
	00 at 200 pct all locations
	sure Protection Type For Which Designed:
	ral purpose
	Release Ambient Tempurature Rating:
	legrees celsius all locations
	iency In Hertz:
60.0 a	II locations
	nal Type And Quantity:
6 com	pression
Shelf	Life:
N/a	
Unit C	Of Measure:
Demil	litarization:
No	
Fiig:	
A030a	a0