NSN 5925-00-733-4565

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-733-4565

Body Style: Rectangular dimensional envelope **Overall Length:** 24.523 inches **Overall Height:** 5.420 inches **Overall Width:** 8.250 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.250 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Features Provided:** Adjustable trip release and current limiter **Maximum Continuous Load Current Rating Per Pole:** 600.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 480.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 100000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-00-733-4565 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+3000.0/+6000.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
20.000 at 200 pct all locations and 32.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
58.000 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0