NSN 5925-00-735-9379

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-735-9379 **Overall Length:** 1.750 inches **Overall Height:** 1.125 inches **Overall Width:** 0.625 inches **Case Material: Plastic Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 0.7 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Reset **Thread Size:**

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 125 pct single location and 4.000 at 125 pct single location

Inclosure Protection Type For Which Designed:

Watertight

NSN 5925-00-735-9379

Circuit Breaker - Page 2 of 2



Frequency In Hertz:
400.0 single location
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0