# NSN 5925-00-738-7301

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-738-7301

### **Overall Length:**

- 4.000 inches
- **Overall Height:**
- 1.969 inches

#### **Overall Width:**

2.125 inches

#### **Case Material:**

Metal

#### **Unthreaded Mounting Hole Diameter:**

0.218 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 3.500 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

#### **Pole Quantity:**

# 1

Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

4 unthreaded hole

#### Maximum Continuous Load Current Rating Per Pole:

200.0 amperes dc single location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

30.0 dc single location

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

4000.0 dc single location

#### **Circuit Protection Type:**

Overcurrent single location

#### **Trip Release Method:**

Magnetic single location

#### **Trip Release Characteristic:**

Time delay single location

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

#### **Actuator Function:**

Reset

#### Trip Delay Time In Seconds Per Rated Continuous Current:

300.000 at 125 pct single location and 40.000 at 200 pct single location and 12.000 at 300 pct single location and 15.000 at 400 pct single location

# NSN 5925-00-738-7301

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:

Dustproof

## Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

## Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0