## NSN 5925-00-739-7374



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-739-7374 **Bushing Length:** 0.250 inches **Body Length:** 2.250 inches **Body Width:** 1.218 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 0.704 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.218 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 threaded bushing w/panel seal Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1200.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 all locations **Reset Method:** 

Trip free

**Main Contact Tripping Mechanism Type:** 

Manual

## **NSN 5925-00-739-7374** Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
3 push button
Actuator Function:
Reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
15.000 at 200 pct all locations and 55.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Vibration resistant and shock resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
150.0 grams
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A030a0