NSN 5925-00-741-1479

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-741-1479 **Body Style:** Single pole type **Body Length:** 1.812 inches **Body Width:** 1.188 inches **Body Height:** 1.875 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.625 inches **Unthreaded Mounting Hole Diameter:** 0.174 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.574 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

50.000 at 200 pct single location and 6.500 at 400 pct single location

Inclosure Protection Type For Which Designed:

Watertight

NSN 5925-00-741-1479

Circuit Breaker - Page 2 of 2



	Trip	Release	Ambient	Tem	purature	Rating:
--	------	---------	----------------	-----	----------	---------

25.0 degrees celsius single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0