## NSN 5925-00-752-6903

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-752-6903

Body Style:
Single pole type
Body Length:
1.891 inches
Body Width:
1.188 inches
Body Height:
1.407 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.844 inches
Unthreaded Mounting Hole Diameter:
0.174 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.574 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
600.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
130.0 single location
Reset Method:
Automatic
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:
50.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**Corrosion resistant and dustproof and fungus resistant

## NSN 5925-00-752-6903

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating	Trip	Release	<b>Ambient</b>	<b>Tempurature</b>	Rating
---	------	---------	----------------	--------------------	--------

25.0 degrees celsius single location

**Terminal Type And Quantity:** 

2 quick disconnect, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0