

View Online at <https://aerobasegroup.com/nsn/5925-00-752-6908>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.000 inches

**Overall Height:**

1.672 inches

**Overall Width:**

1.813 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.174 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac single location and 25.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

30.0 ac single location and 30.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

900.0 ac single location and 900.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3600.000 at 125 pct single location and 30.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Watertight

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Test Data Document:**

81349-mil-c-13516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 quick disconnect, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0