

View Online at <https://aerobasegroup.com/nsn/5925-00-755-5798>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.219 inches and 0.281 inches

Body Length:

2.203 inches

Body Width:

2.250 inches

Body Height:

2.125 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.156 inches and 1.218 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.712 inches and 0.774 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.796 inches and 1.828 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.470 inches and 1.502 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 70.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

8.000 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0