

View Online at <https://aerobasegroup.com/nsn/5925-00-755-7906>

Body Style:

Single pole type

Bushing Length:

0.300 inches

Body Length:

1.375 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.906 inches

Mounting Surface To Terminal End Distance:

1.312 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location and 20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac single location and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 200 pct single location and 70.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Explosion resistant and moisture resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0