## NSN 5925-00-756-0462

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-756-0462 **Overall Length:** 2.317 inches **Overall Height:** 1.094 inches Overall Width: 0.750 inches **Case Material: Plastic Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location and 5.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 200.0 ac single location and 28.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 115.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 push button **Actuator Function:** Reset **Thread Size:** 0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 55.000 at 200 pct single location and 2.000 at 400 pct single location and 7.000 at 400 pct single location

## **Inclosure Protection Type For Which Designed:**

Explosion proof and dustproof

## NSN 5925-00-756-0462

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Precious Material:
Silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0