NSN 5925-00-757-7259

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-757-7259

Body Style:
Rectangular dimensional envelope
Overall Length:
16.000 inches
Overall Height:
4.062 inches
Overall Width:
8.250 inches
Unthreaded Mounting Hole Diameter:
0.344 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
800.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
280.000 at 200 pct all locations and 950.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:

6 compression

NSN 5925-00-757-7259

Circuit Breaker Tripper - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0