# NSN 5925-00-758-5128

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-758-5128

**Overall Length:** 

1.673 inches

**Overall Height:** 

0.434 inches

# **Overall Width:**

0.750 inches

#### **Case Material:**

Plastic

Pole Quantity:

1

#### Mounting Facility Type And Quantity:

1 threaded bushing

#### Storage Type:

General purpose warehouse

## Thready Qty Per Inch (tpi):

28

#### Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac single location

### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

## **Circuit Protection Type:**

Overcurrent single location

#### **Trip Release Method:**

Thermal single location

#### **Trip Release Characteristic:**

Time delay single location

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

#### Manual Actuator Type And Quantity:

1 toggle

#### **Actuator Function:**

Trip-reset

### Actuator Position Designation:

At pole one

### Internal Trip Release Configuration:

Series trip single location

# NSN 5925-00-758-5128

Circuit Breaker - Page 2 of 2



#### **Thread Size:**

0.375 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 40.000 at 200 pct single location

#### **Trip Release Ambient Tempurature Rating:**

21.0 degrees celsius single location

## Frequency In Hertz:

60.0 single location

#### **Thread Series Designator:**

Un

#### **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A030a0