NSN 5925-00-758-6011

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-758-6011

Body Style:

Multipole-multiple actuator type

Bushing Length:

Between 0.235 inches and 0.265 inches

Body Length:

Between 2.188 inches and 2.218 inches

Body Width:

Between 1.203 inches and 1.233 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.688 inches and 0.718 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.735 inches and 0.765 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.812 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1200.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 all locations

Reset Method:

Manual

NSN 5925-00-758-6011

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 3 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One, two, and three linked Internal Trip Release Configuration: Series trip all locations **Thread Size:** 0.469 inches Trip Delay Time In Seconds Per Rated Continuous Current: 15.000 at 200 pct all locations and 55.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Hermetically sealed and shock resistant and vibration resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius all locations Frequency In Hertz: 400.0 all locations **Unpackaged Unit Weight:** 0.360 pounds **Thread Series Designator:** Uns **Terminal Type And Quantity:** 6 tab w/screw Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0