

View Online at <https://aerobasegroup.com/nsn/5925-00-758-6011>

Body Style:

Multipole-multiple actuator type

Bushing Length:

Between 0.235 inches and 0.265 inches

Body Length:

Between 2.188 inches and 2.218 inches

Body Width:

Between 1.203 inches and 1.233 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.688 inches and 0.718 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.735 inches and 0.765 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.812 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1200.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct all locations and 55.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed and shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

0.360 pounds

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0