

View Online at <https://aerobasegroup.com/nsn/5925-00-762-0126>

Body Style:

Multipole-single actuator type

Body Length:

6.500 inches

Body Width:

4.125 inches

Body Height:

3.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.562 inches

Center To Center Distance Between Terminals Parallel To Width:

1.376 inches

Unthreaded Mounting Hole Diameter:

0.198 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.938 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.376 inches

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

44.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

440.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

121.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Switch Location And Position Designation:

External at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

75.000 at 150 pct all locations and 450.000 at 150 pct all locations and 35.000 at 200 pct all locations and 100.000 at 200 pct all locations
and 10.000 at 300 pct all locations and 40.000 at 300 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Switch Terminal Type:

Wire lead

Switch Current Rating And Type In Amps:

10.0 ac and 1.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 50.0 dc

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0