NSN 5925-00-762-0909

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-762-0909

Body Style:

Rectangular dimensional envelope

Overall Length:

22.000 inches

Overall Height:

9.062 inches

Overall Width:

12.000 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

1600.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+4000.0/+12000.0 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

 $0.708\;$ at 200 pct all locations and $0.750\;$ at 200 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-762-0909

Circuit Breaker Tripper - Page 2 of 2

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0

