## NSN 5925-00-766-6576

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-766-6576 **Body Style:** Single pole type **Body Length:** 2.500 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.062 inches **Boss Height:** 0.125 inches **Mounting Surface To Terminal End Distance:** 2.547 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location and 10.0 milliamperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 120.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Nontrip free **Manual Actuator Type And Quantity:** 1 toggle

**Actuator Function:** 

Trip-reset

## **NSN 5925-00-766-6576** Circuit Breaker - Page 2 of 2



<b>Actuator Position Designation:</b>
At pole one
Thread Size:
0.138 inches
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0