## NSN 5925-00-768-0289



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-768-0289 **Body Style:** Rectangular dimensional envelope Overall Length: 15.375 inches **Overall Height:** 4.750 inches **Overall Width:** 8.000 inches **Case Material:** Metal **Unthreaded Mounting Hole Diameter:** 0.344 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 7500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** 

Actuator i

Trip-reset

**Actuator Position Designation:** 

At pole two

## NSN 5925-00-768-0289

Circuit Breaker - Page 2 of 2



## Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct all locations and 0.350 at 200 pct all locations

**Inclosure Protection Type For Which Designed:** 

Fungus resistant

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

6 screw

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A030a0