

View Online at <https://aerobasegroup.com/nsn/5925-00-774-2947>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

0.130 inches

**Body Length:**

2.000 inches

**Body Width:**

1.500 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Mounting Surface To Terminal End Distance:**

2.220 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Handle lock

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

175.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Reset

**Actuator Position Designation:**

Between pole one and two

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

External at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

6.000 at 150 pct all locations and 60.000 at 150 pct all locations and 2.200 at 200 pct all locations and 20.000 at 200 pct all locations and 0.300 at 400 pct all locations and 2.300 at 400 pct all locations

**Switch Terminal Type:**

Solder stud

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0