

View Online at <https://aerobasegroup.com/nsn/5925-00-775-1717>

**Body Style:**

Single pole type

**Overall Length:**

3.160 inches

**Body Width:**

1.880 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.060 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.195 inches and 0.225 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.406 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

2.000 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

150.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

575.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

8.000 at 200 pct single location and 50.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Shock resistant and vibration resistant and salt spray proof and fungus resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Test Data Document:**

81349-mil-c-13516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Specification Data:**

81349--13516/7bii government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0