# NSN 5925-00-775-1717

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-775-1717 **Body Style:** Single pole type **Overall Length:** 3.160 inches **Body Width:** 1.880 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.060 inches **Unthreaded Mounting Hole Diameter:** Between 0.195 inches and 0.225 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.406 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 150.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 575.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 single location **Reset Method:** Automatic

Automatic

Internal Trip Release Configuration:

Series trip single location

# NSN 5925-00-775-1717

Circuit Breaker - Page 2 of 2



#### **Trip Delay Time In Seconds Per Rated Continuous Current:**

8.000 at 200 pct single location and 50.000 at 200 pct single location

### **Inclosure Protection Type For Which Designed:**

Shock resistant and vibration resistant and salt spray proof and fungus resistant

### **Trip Release Ambient Tempurature Rating:**

25.0 degrees celsius single location

### **Test Data Document:**

81349-mil-c-13516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 threaded stud

#### **Specification Data:**

81349--13516/7bii government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A030a0