

View Online at <https://aerobasegroup.com/nsn/5925-00-778-8822>

Body Style:

Multipole-multiple actuator type

Body Length:

3.750 inches

Body Width:

2.000 inches

Body Height:

2.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.250 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

35.000 at 150 pct all locations and 450.000 at 150 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0