

View Online at <https://aerobasegroup.com/nsn/5925-00-782-6946>

**Body Style:**

Multipole-single actuator type

**Body Length:**

Between 8.220 inches and 8.280 inches

**Body Width:**

Between 7.595 inches and 7.655 inches

**Body Height:**

Between 4.782 inches and 4.842 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 6.970 inches and 7.030 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 1.345 inches and 1.405 inches

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.907 inches and 4.967 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 4.813 inches and 4.873 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.313 inches and 0.373 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

600.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

18000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0