

View Online at <https://aerobasegroup.com/nsn/5925-00-791-8676>

Body Style:

Multipole-single actuator type

Body Length:

5.250 inches

Body Width:

2.000 inches

Body Height:

2.687 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.359 inches

Center To Center Distance Between Terminals Parallel To Width:

0.984 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.062 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.984 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.218 inches

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.300 at 200 pct all locations and 1.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

15.0 ac and 0.5 dc

Switch Voltage Rating And Type In Volts:

480.0 ac and 125.0 dc

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0