NSN 5925-00-795-4958

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-795-4958
Body Style:
Rectangular dimensional envelope
Overall Length:
11.000 inches
Overall Height:
6.000 inches
Overall Width:
9.000 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
125.0 amperes ac all locations and 125.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations and 250.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

NSN 5925-00-795-4958

Circuit Breaker Tripper - Page 2 of 2



Unpackaged \	Unit	Weight:
--------------	------	---------

4.000 pounds

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0