NSN 5925-00-796-4439



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-796-4439 **Body Style:** Rectangular dimensional envelope **Overall Length:** 7.531 inches **Overall Height:** 3.500 inches **Overall Width: 3.688** inches **Unthreaded Mounting Hole Diameter:** 0.438 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 unthreaded hole **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 175.0 amperes ac all locations and 175.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations Adjustable Trip Setting Current Range Per Pole In Amps: +650.0/+1300.0 ac all locations and +650.0/+1300.0 dc all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 60.000 at 300 pct all locations and 120.000 at 300 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 6 bus bar Shelf Life: N/a

Unit Of Measure:

NSN 5925-00-796-4439

Circuit Breaker Tripper - Page 2 of 2



Demilitarization:

No

Fiig:

A030a0