

View Online at <https://aerobasegroup.com/nsn/5925-00-798-5229>

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

200.0 amperes ac single location and 200.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 25.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

4000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Automatic

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location and 200.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Explosion resistant

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0