

View Online at <https://aerobasegroup.com/nsn/5925-00-800-1481>

Case Material:

Plastic

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac all locations and 40.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Ultimate Trip Time Per Pole In Seconds:

90.000 all locations and 540.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.250 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct all locations and 102.000 at 200 pct all locations and 10.000 at 300 pct all locations and 28.000 at 300 pct all locations and 6.000 at 400 pct all locations and 14.000 at 400 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Terminal Type And Quantity:

6 quick disconnect, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0