# NSN 5925-00-801-7095

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-801-7095

#### **Body Style:**

Multipole-single actuator type

#### **Body Length:**

10.000 inches

### Body Width:

4.500 inches

#### **Body Height:**

3.844 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

#### 8.750 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.500 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

### Boss Height:

0.188 inches

#### Pole Quantity:

3

# Mounting Facility Type And Quantity:

4 unthreaded hole

# Storage Type:

General purpose warehouse

# Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

# Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

# **Circuit Protection Type:**

Overcurrent all locations

# Trip Release Method:

Thermal-magnetic all locations

# Trip Release Characteristic:

Instantaneous all locations and time delay all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# NSN 5925-00-801-7095

Circuit Breaker - Page 2 of 2



Ultimate Trip Time Per Pole In Seconds: 3600.000 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Trip Delay Time In Seconds Per Rated Continuous Current: 50.000 at 200 pct all locations and 120.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Fungus resistant and moisture resistant **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 6 compression Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0