

View Online at <https://aerobasegroup.com/nsn/5925-00-801-7116>

**Body Style:**

Multipole-single actuator type

**Body Length:**

11.000 inches

**Body Width:**

9.000 inches

**Body Height:**

4.062 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

9.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

8.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

3.000 inches

**Boss Height:**

0.250 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Features Provided:**

Adjustable trip release

**Thready Qty Per Inch (tpi):**

20

**Maximum Continuous Load Current Rating Per Pole:**

175.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

0.360 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+750.0/+1600.0 ac all locations

**Thread Size:**

0.250 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

480.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0