## NSN 5925-00-802-8626

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-802-8626

**Body Style:** Rectangular dimensional envelope **Overall Length:** 3.344 inches **Overall Height:** 1.000 inches **Overall Width:** 3.094 inches **Case Material:** Plastic **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Ultimate Trip Time Per Pole In Seconds:** 80.000 single location and 380.000 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

**Manual Actuator Type And Quantity:** 

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole one

## NSN 5925-00-802-8626

Circuit Breaker - Page 2 of 2



## **Trip Delay Time In Seconds Per Rated Continuous Current:**

120.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:** 

Corrosion resistant

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

**Terminal Type And Quantity:** 

1 compression and 1 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A030a0