## NSN 5925-00-803-5488

Circuit Breaker Tripper - Page 1 of 2



View On	line at https://aerobaseg	roup.com/nsn/5	925-00-803-5488	į	
Body St	yle:				
Rectang	ular dimensional envelop	e			
Overall	_ength:				
4.500 inc	ches				
Overall	Height:				

**Overall Width:** 

4.500 inches

8.250 inches

**Unthreaded Mounting Hole Diameter:** 

0.375 inches

**End Application:** 

Used in circuit breaker nsn 5925-01-075-8931 onboard 270 ft. Wmec coast guard vessels

**Pole Quantity:** 

**Mounting Facility Type And Quantity:** 

3 unthreaded hole

**Features Provided:** 

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:** 

150.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

500.0 ac all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Thermal all locations

**Trip Release Characteristic:** 

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

150.0 all locations

**Ultimate Trip Time Per Pole In Seconds:** 

3600.000 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+625.0/+1300.0 ac all locations

**Internal Trip Release Configuration:** 

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:** 

100.000 at 200 pct all locations and 300.000 at 200 pct all locations

**Trip Release Ambient Tempurature Rating:** 

50.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

## NSN 5925-00-803-5488

Circuit Breaker Tripper - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

6 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0