

View Online at <https://aerobasegroup.com/nsn/5925-00-804-4412>

Body Style:

Rectangular dimensional envelope

Overall Length:

6.125 inches

Overall Height:

2.750 inches

Overall Width:

3.219 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations and 30.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Thread Size:

0.190 inches

Inclosure Protection Type For Which Designed:

Vibration resistant and general purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0