

View Online at <https://aerobasegroup.com/nsn/5925-00-809-2335>

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.175 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

130.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Trip Delay Time In Seconds Per Rated Continuous Current:**

240.000 at 150 pct all locations and 50.000 at 200 pct all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 eyelet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0