

View Online at <https://aerobasegroup.com/nsn/5925-00-810-4898>

Body Style:

Single pole type

Body Length:

6.310 inches

Body Width:

2.750 inches

Body Height:

3.380 inches

Case Material:

Plastic

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac all locations and 40.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations and 7500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Trip Release Duty Cycle:

Continuous all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

92.000 at 150 pct all locations and 400.000 at 150 pct all locations and 30.000 at 200 pct all locations and 90.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0